

Order No.

Part designation Version

EAN Qty.

Can be labelled with thermal transfer print Can be printed with plotter Can be written with dot-matrix printer Can be written with laser printer Colour of printing Function Length Material Material colour Material colour according to resistance co Max. temperature, continuous Min. temperature, continuous No. per sheet Orientation of print Pin can be written (STI) Pitch PrintJet Printed characters Printing method Speed marking laser Type of printing

Adhesive

Width

1630150001 KSW 4 16/3,5 1-16 Connector markers, L x W: 56 x 4 mm, Polyester, PVC-free, white 4008190214555 10 pc(s).

	Acrylate
nters	No
	No
	No
	No
	black
	Device and installation markers
	56 mm
	Polyester, PVC-free
	white
ode	9
	150 °C
	-40 °C
	20 pcs
	horizontal
	No
	3.5 mm
	No
	Numbers
	Thermotransfer
	No
	Standard
	4 mm

Approvals institutes

n.a.

- 1 -



Approvals

Classifications	
ETIM 2.0	EC000761
ETIM 3.0	EC000761
eClass 4.1	24-19-02-19
eClass 5.0	27-14-11-37
eClass 5.1	27-14-11-37

Similar products

Order No.		
1630190001	KSW 4 8/3,5 1-8	Connector markers, L x W: 28 x 4 mm, Polyester, PVC-free, white
1640410001	KSW 4 24/3,5 W 1-24	Connector markers, L x W: 84 x 4 mm, Polyester, PVC-free, white

